# DUPONT™ TYCHEM® 6000 F

## TECHNICAL DATA SHEET

CAT III
T3
T4
T5
T6
EN 1073-2
EN 1149-5
EN 14126

## PRODUCT INFORMATION

DuPont™ Tychem® 6000 F CHA5. Durable yet lightweight protection against a wide range of toxic industrial chemicals, particulates, and biohazards in a grey hooded coverall. Features stitched and over-taped seams, a respirator fit two-piece hood, elasticated wrists, ankles, face and waist, thumb loops, a pin lock slider zipper pull, and double storm flaps with an adhesive outer flap and chin flap. Suitable for a variety of applications, including chemical spill clean-up, emergency response, military and petrochemical operations.

## ATTRIBUTES

| | |
|---|---|
| **Full Part Number** | TFCHA5TGY00 |
| **Fabric/Materials** | Tychem® F |
| **Design** | Hooded coverall with elastics and thumb loops |
| **Seam** | Stitched and over-taped |
| **Color** | Grey |
| **Other Colors** | Orange |
| **Sizes** | SM, MD, LG, XL, 2X, 3X |
| **Quantity/Box** | 25 per box, individually packed. |

## FEATURES

- Certified according to Regulation (EU) 2016/425.
- Chemical protective clothing, Category III, Type 3-B, 4-B, 5-B and 6-B.
- EN 14126 (barrier to infective agents), EN 1073-2 (protection against radioactive contamination)..
- Antistatic treatment (EN 1149-5) - on inside
- Stitched and over-taped seams with barrier tape for protection and strength
- Self-adhesive double zipper flap closure system for higher protection
- Option: Socks attached to the ankle: to be worn inside safety boots or shoes with additional knee-length boot flap to ensure a high protection level

### SIZETABLE

| PRODUCT SIZE | ARTICLE NUMBER | ADDITIONAL INFO |
|---|---|---|
| SM | D13495186 | |
| MD | D13495156 | |
| LG | D13395221 | |
| XL | D13395545 | |
| 2X | D13395268 | |
| 3X | D13495118 | |

### PHYSICAL PROPERTIES

| PROPERTY | TEST METHOD | TYPICAL RESULT | EN |
|---|---|---|---|
| Abrasion Resistance [7] | EN 530 Method 2 | >2000 cycles | 6/6 [1] |
| Basis Weight | DIN EN ISO 536 | 120 g/m$^2$ | N/A |
| Bursting Strength (Mullenburst) | ISO 2758 | 650 kPa | N/A |
| Colour | N/A. | Grey | N/A |

| PROPERTY | TEST METHOD | TYPICAL RESULT | EN |
|---|---|---|---|
| Flex Cracking Resistance [7] | EN ISO 7854 Method B | >1000 cycles | 1/6 [1] |
| Puncture Resistance | EN 863 | >10 N | 2/6 [1] |
| Resistance to water penetration | AATCC 127 | >30 kPa | N/A |
| Surface Resistance at RH 25%, inside [7] | EN 1149-1 | < 2,5 • $10^9$ Ohm | N/A |
| Surface Resistance at RH 25%, outside [7] | EN 1149-1 | No antistatic treatment | N/A |
| Tensile Strength (MD) | DIN EN ISO 13934-1 | >100 N | 3/6 [1] |
| Tensile Strength (XD) | DIN EN ISO 13934-1 | >100 N | 3/6 [1] |
| Thickness | DIN EN ISO 534 | 220 µm | N/A |
| Trapezoidal Tear Resistance (MD) | EN ISO 9073-4 | >20 N | 2/6 [1] |
| Trapezoidal Tear Resistance (XD) | EN ISO 9073-4 | >20 N | 2/6 [1] |

1 According to EN 14325 | 2 According to EN 14126 | 3 According to EN 1073-2 | 4 According to EN ISO 14116 | 12 According to EN ISO 11612 |
5 Front Tyvek ® / Back | 6 Based on test according to ASTM D-572 | 7 See Instructions for Use for further information, limitations and warnings | > Larger than |
< Smaller than | <= Smaller than or equal to | N/A Not Applicable | STD DEV Standard Deviation |

## GARMENT PERFORMANCE

| PROPERTY | TEST METHOD | TYPICAL RESULT | EN |
|---|---|---|---|
| Type 3: Resistance to Penetration by Liquids (Jet Test). | EN 17491-3 | Pass | N/A |
| Type 4: Resistance to Penetration by Liquids (High Level Spray Test). | EN ISO 17491-4, Method B | Pass | N/A |
| Type 5: Inward Leakage of Airborne Solid Particulates | EN ISO 13982-2 | Pass | N/A |
| Type 6: Resistance to Penetration by Liquids (Low Level Spray Test) | EN ISO 17491-4, Method A | Pass | N/A |
| Nominal protection factor [7] | EN 1073-2 | >5 | 1/3 [3] |
| Shelf Life [7] | N/A. | 10 years [6] | N/A |
| Seam Strength | EN ISO 13935-2 | >125 N | 4/6 [1] |

1 According to EN 14325 | 3 According to EN 1073-2 | 12 According to EN ISO 11612 | 13 According to EN 11611 | 5 Front Tyvek ® / Back |
6 Based on test according to ASTM D-572 | 7 See Instructions for Use for further information, limitations and warnings |
11 Based on the average of 10 suits, 3 activities, 3 probes | > Larger than | < Smaller than | <= Smaller than or equal to | N/A Not Applicable |
* Based on lowest single value |

## PENETRATION AND REPELLENCY

| PROPERTY | TEST METHOD | TYPICAL RESULT | EN |
|---|---|---|---|
| Repellency to Liquids, o-Xylene | EN ISO 6530 | >95 % | 3/3 [1] |
| Repellency to Liquids, Butan-1-ol | EN ISO 6530 | >95 % | 3/3 [1] |
| Repellency to Liquids, Sodium Hydroxide (10%) | EN ISO 6530 | >95 % | 3/3 [1] |
| Repellency to Liquids, Sulphuric Acid (30%) | EN ISO 6530 | >95 % | 3/3 [1] |
| Resistance to Penetration by Liquids, Butan-1-ol | EN ISO 6530 | <1 % | 3/3 [1] |
| Resistance to Penetration by Liquids, o-Xylene | EN ISO 6530 | <1 % | 3/3 [1] |
| Resistance to Penetration by Liquids, Sodium Hydroxide (10%) | EN ISO 6530 | <1 % | 3/3 [1] |
| Resistance to Penetration by Liquids, Sulphuric Acid (30%) | EN ISO 6530 | <1 % | 3/3 [1] |

1 According to EN 14325 | > Larger than | < Smaller than | <= Smaller than or equal to |

## BIOLOGICAL BARRIER

| PROPERTY | TEST METHOD | TYPICAL RESULT | EN |
|---|---|---|---|
| Resistance to Penetration by Biologically Contaminated Aerosols | ISO/DIS 22611 | log ratio >5 | 3/3 [2] |

| PROPERTY | TEST METHOD | TYPICAL RESULT | EN |
|---|---|---|---|
| Resistance to Penetration by Blood and Body Fluids using Synthetic Blood | ISO 16603 | 20 kPa | 6/6 [2] |
| Resistance to Penetration by Blood-borne Pathogens using Bacteriophage Phi-X174 | ISO 16604 Procedure C | 20 kPa | 6/6 [2] |
| Resistance to Penetration by Contaminated Liquids | EN ISO 22610 | >75 min | 6/6 [2] |
| Resistance to Penetration by Contaminated Solid Particles | ISO 22612 | log cfu <1 | 3/3 [2] |

1 According to EN 14325 | > Larger than | < Smaller than | <= Smaller than or equal to |

PERMEATION DATA DUPONT™ TYCHEM® 6000 F

| HAZARD / CHEMICAL NAME | PHYSICAL STATE | CAS | BT ACT | BT 0.1 | BT 1.0 | EN | SSPR | MDPR | CUM 480 | TIME 150 | ISO |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 1-Bromobutane | Liquid | 109-65-9 | >480 | >480 | >480 | 6 | <0.04 | 0.04 | <20 | >480 | 6 |
| 2,5-Dimethoxytetrahydrofuran | Liquid | 696-59-3 | >480 | >480 | >480 | 6 | <0.04 | 0.04 | <20 | >480 | 6 |
| 2-(2-Butoxyethoxy) ethanol | Liquid | 112-34-5 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| 2-Methyl-2-Butanol | Liquid | 75-85-4 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| 2-Methyl-4-isothiazolin-3-one (20%) | Liquid | 2682-20-4 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| 2-Methyltetrahydrofuran | Liquid | 96-47-9 | >480 | >480 | >480 | 6 | <0.04 | 0.04 | <20 | >480 | 6 |
| Acetaldehyde | Liquid | 75-07-0 | imm | imm | 13*/23 | 1 | 2 | 0.06 | | | |
| Acetic acid (>95%) | Liquid | 64-19-7 | >480 | >480 | >480 | 6 | <0.08 | 0.08 | <38.4 | >480 | 6 |
| Acetic acid 2 ethoxy ethyl ester | Liquid | 111-15-9 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Acetic acid 2 methoxy ethyl ester | Liquid | 110-49-6 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Acetic acid ethenyl ester | Liquid | 108-05-4 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Acetic acid ethyl ester | Liquid | 141-78-6 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Acetic acid pentyl ester | Liquid | 628-63-7 | >480 | >480 | >480 | 6 | 0.007 | 0.001 | <10.2 | >480 | 6 |
| Acetic anhydride | Liquid | 108-24-7 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Acetic chloride | Liquid | 75-36-5 | 155 | >480 | >480 | 6 | 0.0014 | 0.0001 | | | |
| Acetone | Liquid | 67-64-1 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Acetone cyanohydrin | Liquid | 75-86-5 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Acetonitrile | Liquid | 75-05-8 | 65*/83 | 131 | >480 | 6 | <0.4 | 0.03 | <82 | >480 | 6 |
| Acetyl chloride | Liquid | 75-36-5 | 155 | >480 | >480 | 6 | 0.0014 | 0.0001 | | | |
| Acroleic acid | Liquid | 79-10-7 | >480 | >480 | >480 | 6 | <0.06 | 0.06 | <28.8 | >480 | 6 |
| Acrolein | Liquid | 107-02-8 | 51*/65 | 75*/101 | >480 | 6 | <0.5 | 0.02 | 105 | >480 | 6 |
| Acrolein (10 g/m$^2$) | Liquid | 107-02-8 | >480 | >480 | >480 | 6 | <0.04 | 0.04 | <19.2 | >480 | 6 |
| Acrylamide (50%) | Liquid | 79-06-1 | >480 | >480 | >480 | 6 | <0.1 | 0.1 | <48 | >480 | 6 |
| Acrylic acid | Liquid | 79-10-7 | >480 | >480 | >480 | 6 | <0.06 | 0.06 | <28.8 | >480 | 6 |
| Acrylic acid ethyl ester | Liquid | 140-88-5 | imm* /161 | imm* /162 | imm* /163 | | <5 | 0.04 | | | |
| Acrylic acid n-butyl ester | Liquid | 141-32-2 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | >480 | >480 | 6 |
| Acrylicamide (50%) | Liquid | 79-06-1 | >480 | >480 | >480 | 6 | <0.1 | 0.1 | <48 | >480 | 6 |
| Acrylonitrile | Liquid | 107-13-1 | 72*/91 | 73*/92 | 103 | 3 | 8.9 | 0.0085 | | | |
| Acryloyl Chloride | Liquid | 814-68-6 | 166*/224 | 334 | >480 | 6 | <0.3 | 0.04 | 29.6 | >480 | 6 |
| Adipic acid dinitrile | Liquid | 111-69-3 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Adipic acid nitrile | Liquid | 111-69-3 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Adiponitrile | Liquid | 111-69-3 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Allyl alcohol | Liquid | 107-18-6 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Allyl chloride | Liquid | 107-05-1 | 291*/400 | 381*/447 | >480 | 6 | <0.2 | 0.02 | <18.5 | >480 | 6 |
| Amido sulfonic acid (15%) | Liquid | 5329-14-6 | >480 | >480 | >480 | 6 | <0.04 | 0.04 | <19.2 | >480 | 6 |

| HAZARD / CHEMICAL NAME | PHYSICAL STATE | CAS | BT ACT | BT 0.1 | BT 1.0 | EN | SSPR | MDPR | CUM 480 | TIME 150 | ISO |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Amino benzene | Liquid | 62-53-3 | >480 | >480 | >480 | 6 | <0.03 | 0.03 | <14.4 | >480 | 6 |
| Amino diphenyl, 4- (1 mg /ml in Methanol) | Liquid | 92-67-1 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Amino ethanol, 2- | Liquid | 141-43-5 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Amino ethylethanolamine | Liquid | 111-41-1 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Amino ethylethanolamine (60%) | Liquid | 111-41-1 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Amino ethylpiperazine | Liquid | 140-31-8 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Amino propane, 2- | Liquid | 75-31-0 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Ammonia (-33 °C, liquid) | Liquid | 7664-41-7 | 15 | 20 | >480 | 6 | <0.89 | 0.04 | 109 | >480 | 6 |
| Ammonia (gaseous) | Vapor | 7664-41-7 | 20 | 20 | 21 | 1 | 1.5 | 0.0024 | | | |
| Ammonium bifluoride (sat) | Liquid | 1341-49-7 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Ammonium fluoride (40%) | Liquid | 12125-01-8 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Ammonium hydrogendifluoride (sat) | Liquid | 1341-49-7 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Ammonium hydroxide (32%) | Liquid | 1336-21-6 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Amyl acetate, n- | Liquid | 628-63-7 | >480 | >480 | >480 | 6 | 0.007 | 0.001 | <10.2 | >480 | 6 |
| Amyl alcohol | Liquid | 71-41-0 | >480 | >480 | >480 | 6 | <0.1 | 0.1 | <48 | >480 | 6 |
| Amyl alcohol, tert- | Liquid | 75-85-4 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Amyl ester acetic acid | Liquid | 628-63-7 | >480 | >480 | >480 | 6 | 0.007 | 0.001 | <10.2 | >480 | 6 |
| Anilin, 4- Trifluoromethoxy- | Liquid | 461-82-5 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Aniline | Liquid | 62-53-3 | >480 | >480 | >480 | 6 | <0.03 | 0.03 | <14.4 | >480 | 6 |
| Anthracene (sat in Toluene) | Liquid | 120-12-7 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Anthracin (sat in Toluene) | Liquid | 120-12-7 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Antimony pentachloride | Liquid | 7647-18-9 | <15 | <15 | <15 | 1 | >10 | 0.1 | | | |
| Arsenic (III) chloride | Liquid | 7784-34-1 | 22*/29 | 32*/38 | 59 | 2 | 334 | 0.01 | | | |
| Arsenic trichloride | Liquid | 7784-34-1 | 22*/29 | 32*/38 | 59 | 2 | 334 | 0.01 | | | |
| Azolidine | Liquid | 123-75-1 | 40*/80 | 45*/100 | 145*/185 | 4 | 4.7 | 0.05 | | | |
| Benzaldehyde | Liquid | 100-52-7 | >480 | >480 | >480 | 6 | <0.03 | 0.03 | <14.4 | >480 | 6 |
| Benzenamine | Liquid | 62-53-3 | >480 | >480 | >480 | 6 | <0.03 | 0.03 | <14.4 | >480 | 6 |
| Benzene | Liquid | 71-43-2 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Benzene carbonyl chloride | Liquid | 98-88-4 | >480 | >480 | >480 | 6 | <0.08 | 0.08 | <38.4 | >480 | 6 |
| Benzene sulfone chloride | Liquid | 98-09-9 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Benzene sulfonyl chloride | Liquid | 98-09-9 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Benzisothiazol 1,2- (20%) | Liquid | 2634-33-5 | >480 | >480 | >480 | 6 | <0.061 | 0.061 | <30 | >480 | 6 |
| Benzo nitrile | Liquid | 100-47-0 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Benzoyl chloride | Liquid | 98-88-4 | >480 | >480 | >480 | 6 | <0.08 | 0.08 | <38.4 | >480 | 6 |
| Benzyl alcohol | Liquid | 100-51-6 | >480 | >480 | >480 | 6 | <0.1 | 0.1 | <48 | >480 | 6 |
| Benzyl chloride | Liquid | 100-44-7 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Benzyl cyanide | Liquid | 140-29-4 | >390 | >390 | >390 | 5 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Benzyl methylamine, N- | Liquid | 103-67-3 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Bis (4-(2,3-epoxypropoxy) phenyl)propane | Liquid | 1675-54-3 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Bis phenol A diglycidyl ether | Liquid | 1675-54-3 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Black Liquor (mix) | Liquid | mix | | >480 | | | | | | | |
| Boron fluoride ethyl ether | Liquid | 109-63-7 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |

| HAZARD / CHEMICAL NAME | PHYSICAL STATE | CAS | BT ACT | BT 0.1 | BT 1.0 | EN | SSPR | MDPR | CUM 480 | TIME 150 | ISO |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Boron trifluoride diethyl etherate | Liquid | 109-63-7 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Boron trifluoride dimethyl etherate | Liquid | 353-42-4 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Boron trifluoride etherate | Liquid | 109-63-7 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Brom thiophene, 2- | Liquid | 1003-09-4 | >480 | >480 | >480 | 6 | <0.03 | 0.03 | <14.4 | >480 | 6 |
| Bromine | Liquid | 7726-95-6 | imm | imm | imm | | 105 | 0.001 | | | |
| Bromo 4-fluorobenzene, 1- | Liquid | 460-00-4 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Bromo fluorobenzene, 4- | Liquid | 460-00-4 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| But-3-en-2-one | Liquid | 78-94-4 | 287*/379 | >480 | >480 | 6 | <0.1 | 0.02 | <9.6 | >480 | 6 |
| Butadiene, 1,3- (gaseous) | Vapor | 106-99-0 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Butanal, n- | Liquid | 123-72-8 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Butanol, 1- | Liquid | 71-36-3 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Butanol, n- | Liquid | 71-36-3 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Butanol, tert- | Liquid | 75-65-0 | 10*/147 | 37*/205 | >480 | 6 | 0.26 | 0.02 | | | |
| Butanone | Liquid | 78-93-3 | imm | 40*/64 | >480 | 6 | 0.36 | 0.001 | | | |
| Butanone oxime, 2- | Liquid | 96-29-7 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Butenal, 2- | Liquid | 123-73-9 | 121 | 147 | >480 | 6 | <1 | 0.02 | 210 | 405 | 5 |
| Butoxy ethanol, 2- | Liquid | 111-76-2 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Butyl acetate, n- | Liquid | 123-86-4 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Butyl acrylate, n- | Liquid | 141-32-2 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | >480 | >480 | 6 |
| Butyl alcohol, n- | Liquid | 71-36-3 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Butyl amine | Liquid | 109-73-9 | 170 | 200 | >480 | 6 | 0.84 | 0.01 | 137.5 | >480 | 6 |
| Butyl ether, n- | Liquid | 142-96-1 | 223*/285 | 223*/285 | 224*/287 | 4 | 14.6 | 0.021 | | | |
| Butyl stannium trichloride | Liquid | 1118-46-3 | >480 | >480 | >480 | 6 | <0.0001 | 0.0001 | <0.04 | >480 | 6 |
| Butylchloroformate | Liquid | 592-34-7 | >480 | >480 | >480 | 6 | <0.07 | 0.07 | <33.6 | >480 | 6 |
| Butyraldehyde, n- | Liquid | 123-72-8 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Butyric Acid | Liquid | 107-92-6 | >480 | >480 | >480 | 6 | <0.07 | 0.07 | <33.6 | >480 | 6 |
| Calomel (sat) | Liquid | 10112-91-1 | >480 | >480 | >480 | 6 | <0.1 | 0.1 | <48 | >480 | 6 |
| Carbon disulfide | Liquid | 75-15-0 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Carbon tetrachloride | Liquid | 56-23-5 | imm | imm*/11 | >480 | 6 | 0.57 | 0.001 | | | |
| Carbon tetrachloride (1000 ppm) | Vapor | 56-23-5 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Caustic ammonia (32%) | Liquid | 1336-21-6 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Caustic soda (50% at 50 ° C) | Liquid | 1310-73-2 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Caustic soda (50%) | Liquid | 1310-73-2 | >480 | >480 | >480 | 6 | <0.025 | 0.025 | <12 | >480 | 6 |
| Cellosolve acetate | Liquid | 110-80-5 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Chemguard S-764P14A | Liquid | mix | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <5 | >480 | 6 |
| Chlor allylene | Liquid | 107-05-1 | 291*/400 | 381*/447 | >480 | 6 | <0.2 | 0.02 | <18.5 | >480 | 6 |
| Chlor trinitromethan | Liquid | 76-06-2 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Chlorine (gaseous) | Vapor | 7782-50-5 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Chloro 1,3-butadiene, 2- (50% in Butanol) | Liquid | 126-99-8 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Chloro 1-methylbenzene, 2- | Liquid | 95-49-8 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Chloro 2,3-epoxy propane, 1- | Liquid | 106-89-8 | 355 | 395 | >480 | 6 | <0.4 | 0.02 | 18.4 | >480 | 6 |
| Chloro 2-nitrobenzene, 1- (35-40 °C, molten) | Liquid | 88-73-3 | >480 | >480 | >480 | 6 | <0.1 | 0.1 | <48 | >480 | 6 |
| Chloro acetic acid (80%) | Liquid | 79-11-8 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |

| HAZARD / CHEMICAL NAME | PHYSICAL STATE | CAS | BT ACT | BT 0.1 | BT 1.0 | EN | SSPR | MDPR | CUM 480 | TIME 150 | ISO |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Chloro acetone (95%) | Liquid | 78-95-5 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Chloro acrylonitrile, 2- | Liquid | 920-37-6 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Chloro aniline, p- (70 °C, molten) | Liquid | 106-47-8 | | imm | 11 | 1 | 256 | 0.0206 | | | |
| Chloro benzenamine, 4- (70 °C, molten) | Liquid | 106-47-8 | | imm | 11 | 1 | 256 | 0.0206 | | | |
| Chloro benzene | Liquid | 108-90-7 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Chloro ethanol, 2- | Liquid | 107-07-3 | >480 | >480 | >480 | 6 | <0.06 | 0.06 | <28.8 | >480 | 6 |
| Chloro ethene | Vapor | 75-01-4 | imm | >480 | >480 | 6 | 0.02 | 0.001 | <9.6 | >480 | 6 |
| Chloro methyl methyl ether | Liquid | 107-30-2 | imm*/11 | imm*/37 | >480 | 6 | 0.75 | 0.001 | | | |
| Chloro picrin | Liquid | 76-06-2 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Chloro prene, 3- | Liquid | 107-05-1 | 291*/400 | 381*/447 | >480 | 6 | <0.2 | 0.02 | <18.5 | >480 | 6 |
| Chloro propan-2-one, 1- (95%) | Liquid | 78-95-5 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Chloro toluene, alpha- | Liquid | 100-44-7 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Chloro toluene, o- | Liquid | 95-49-8 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Chloroacetic ethylester | Liquid | 105-39-5 | >480 | >480 | >480 | 6 | <0.06 | 0.06 | <28.8 | >480 | 6 |
| Chloroacetic ethylester (75% in Ethanol) | Liquid | 105-39-5 | >480 | | | | | | | | |
| Chloroform | Liquid | 67-66-3 | imm | imm | imm | | 10.6 | 0.001 | | | |
| Chloroform (1000 ppm) | Vapor | 67-66-3 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Chlorsulfonic acid | Liquid | 7790-94-5 | 423 | >480 | >480 | 6 | 0.0003 | 0.0001 | | | |
| Chromic acid (CrO3) (44.9%) | Liquid | 1333-82-0 | >480 | >480 | >480 | 6 | <0.07 | 0.07 | <33.6 | >480 | 6 |
| Citric acid (sat) | Liquid | 77-92-9 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Creosote | Liquid | 8001-58-9 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Cresol o- | Liquid | 95-48-7 | 173 | 179 | 211 | 4 | <4 | 0.02 | 674 | 295 | 5 |
| Cresols, mixed isomers | Liquid | 1319-77-3 | >480 | >480 | >480 | 6 | <0.03 | 0.03 | <14.4 | >480 | 6 |
| Cresylic acid | Liquid | 1319-77-3 | >480 | >480 | >480 | 6 | <0.03 | 0.03 | <14.4 | >480 | 6 |
| Croton aldehyde | Liquid | 123-73-9 | 121 | 147 | >480 | 6 | <1 | 0.02 | 210 | 405 | 5 |
| Cumene | Liquid | 98-82-8 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Cyanamide (50%) | Liquid | 420-04-2 | 62*/208 | nm | >480 | 6 | na | 0.17 | <81.6 | >480 | 6 |
| Cyanobenzene | Liquid | 100-47-0 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Cyanoethylene | Liquid | 107-13-1 | 72*/91 | 73*/92 | 103 | 3 | 8.9 | 0.0085 | | | |
| Cyanomethane | Liquid | 75-05-8 | 65*/83 | 131 | >480 | 6 | <0.4 | 0.03 | <82 | >480 | 6 |
| Cyanopropan-2-ol, 2- | Liquid | 75-86-5 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Cyclo hexane | Liquid | 110-82-7 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Cyclo hexanone | Liquid | 108-94-1 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Dahlgren Decon solution | Liquid | mix | >480 | >480 | >480 | 6 | <0.025 | 0.025 | <12 | >480 | 6 |
| Diamino sulfo chloride | Liquid | 13360-57-1 | >480 | >480 | >480 | 6 | <0.04 | 0.04 | <19.2 | >480 | 6 |
| Diaminoethane, 1,2- | Liquid | 107-15-3 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Dibromoethane, 1,2- | Liquid | 106-93-4 | 84*/153 | 144*/288 | >480 | 6 | 0.52 | 0.001 | | | |
| Dibutyl 1,2-benzenedicarboxylate | Liquid | 84-74-2 | | nm | >480 | 6 | | 0.05 | | | |
| Dibutyl phthalate | Liquid | 84-74-2 | | nm | >480 | 6 | | 0.05 | | | |
| Dibutyl sebacate | Liquid | 109-43-3 | | nm | >480 | 6 | <1 | 1 | | | |
| Dichlorbenzen, 1,2- | Liquid | 95-50-1 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Dichlorbenzen, 1,3- | Liquid | 541-73-1 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Dichlorbenzen, 1,4- (50% in Ethanol) | Liquid | 106-46-7 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |

| HAZARD / CHEMICAL NAME | PHYSICAL STATE | CAS | BT ACT | BT 0.1 | BT 1.0 | EN | SSPR | MDPR | CUM 480 | TIME 150 | ISO |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Dichlorethane, 1.2.- | Liquid | 107-06-2 | 65*/83 | 93 | 109 | 3 | <3 | 0.04 | 898 | 182 | 4 |
| Dichloro -2-propanone, 1,3- (45 °C, molten) | Liquid | 534-07-6 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Dichloro acetone, 1,3- (45 ° C, molten) | Liquid | 534-07-6 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Dichloro acetyl chloride | Liquid | 79-36-7 | 160 | 160 | 180 | 4 | 78.41 | 0.01 | | | |
| Dichloro ethyl ether | Liquid | 111-44-4 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Dichloro ethylene, 1,1- | Liquid | 75-35-4 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Dichloro methane | Liquid | 75-09-2 | imm | imm | imm | | 23.7 | 0.03 | | | |
| Dichloro methane (10.000 ppm) | Vapor | 75-09-2 | imm | 52 | >480 | 6 | <0.21 | 0.05 | 100 | >480 | 6 |
| Dichloro methane (1000 ppm) | Vapor | 75-09-2 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Dichloro propene, 2,3- | Liquid | 78-88-6 | imm | imm*/25 | 54*/143 | 2 | 2.4 | 0.001 | | | |
| Dicyanobutane, 1,4- | Liquid | 111-69-3 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Diesel Fuel Grade D-2 | Liquid | mix | >480 | >480 | >480 | 6 | <0.03 | 0.03 | <14.4 | >480 | 6 |
| Diesel fuel | Liquid | 68334-30-5 | 8*/323 | >480 | >480 | 6 | 0.02 | 0.001 | | | |
| Diethyl amine | Liquid | 109-89-7 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Diethyl benzene (95%) | Liquid | 25340-17-4 | >480 | >480 | >480 | 6 | <0.0216 | 0.0216 | <10.4 | >480 | 6 |
| Diethyl ethanamine, N,N- | Liquid | 121-44-8 | >480 | >480 | >480 | 6 | 0.05 | 0.05 | <24 | >480 | 6 |
| Diethyl ether | Liquid | 60-29-7 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Diethyl sulfate | Liquid | 64-67-5 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Diethylene glycol monobutyl ether | Liquid | 112-34-5 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Diethylene triamine | Liquid | 111-40-0 | imm | >480 | >480 | 6 | <0.01 | 0.005 | <4.8 | >480 | 6 |
| Diisopropyl L-tartrate | Liquid | 2217-15-4 | >480 | >480 | >480 | 6 | <0.04 | 0.0377 | 0 | >480 | 6 |
| Diketene Acetone (95%) | Liquid | 5394-63-8 | >480 | >480 | >480 | 6 | <0.0229 | 0.0229 | <11 | >480 | 6 |
| Dimethyl Carbonate (DMC) | Liquid | 616-38-6 | >480 | >480 | >480 | 6 | <0.021 | 0.021 | 0 | >480 | 6 |
| Dimethyl acetamide, N,N- | Liquid | 127-19-5 | >480 | >480 | >480 | 6 | <0.014 | 0.014 | <6.7 | >480 | 6 |
| Dimethyl amine | Vapor | 124-40-3 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Dimethyl aniline, N,N- | Liquid | 121-69-7 | >480 | >480 | >480 | 6 | <0.1 | 0.1 | <48 | >480 | 6 |
| Dimethyl dichlorosilane | Liquid | 75-78-5 | >480 | >480 | >480 | 6 | <0.0001 | 0.0001 | <0.04 | >480 | 6 |
| Dimethyl formamide, N,N- | Liquid | 68-12-2 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Dimethyl fumarate (27 °C, solid) | Solid | 624-49-7 | >480 | nm | >480 | 6 | <0.39 | 0.39 | | | |
| Dimethyl fumarate (37 °C, solid) | Solid | 624-49-7 | >480 | nm | >480 | 6 | <0.39 | 0.39 | | | |
| Dimethyl ketal | Liquid | 67-64-1 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Dimethyl ketone | Liquid | 67-64-1 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Dimethyl nitrosamine | Liquid | 62-75-9 | >480 | >480 | >480 | 6 | <0.001 | 0.001 | <0.48 | >480 | 6 |
| Dimethyl phenylamine, N, N- | Liquid | 121-69-7 | >480 | >480 | >480 | 6 | <0.1 | 0.1 | <48 | >480 | 6 |
| Dimethyl phosphite | Liquid | 868-85-9 | >480 | >480 | >480 | 6 | <0.1 | 0.012 | 0 | >480 | 6 |
| Dimethyl propandioate | Liquid | 108-59-8 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Dimethyl sulfate | Liquid | 77-78-1 | >480 | >480 | >480 | 6 | <0.09 | 0.09 | <43.2 | >480 | 6 |
| Dimethyl sulfide | Liquid | 75-18-3 | 83*/139 | 271 | 452 | 5 | 1.21 | 0.02 | | | |
| Dimethyl sulfoxide | Liquid | 67-68-5 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Dimethylmalonate | Vapor | 108-59-8 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Dioxane, 1,4- | Liquid | 123-91-1 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Diphenyl methane diisocyanate, 4,4'- (50 °C, molten) | Liquid | 101-68-8 | >480 | >480 | >480 | 6 | <0.0403 | 0.0403 | <19.3 | >480 | 6 |

| HAZARD / CHEMICAL NAME | PHYSICAL STATE | CAS | BT ACT | BT 0.1 | BT 1.0 | EN | SSPR | MDPR | CUM 480 | TIME 150 | ISO |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Diphosgene | Liquid | 503-38-8 | >480 | >480 | >480 | 6 | <0.04 | 0.04 | <19.2 | >480 | 6 |
| Dowtherm Heat Transfer Fluid | Liquid | mix | >480 | >480 | >480 | 6 | <0.0267 | 0.0267 | <13 | >480 | 6 |
| Dytek® A | Liquid | 15520-10-2 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Epichlorohydrin | Liquid | 106-89-8 | 355 | 395 | >480 | 6 | <0.4 | 0.02 | 18.4 | >480 | 6 |
| Epoxy ethane (gaseous) | Vapor | 75-21-8 | 106 | 126 | >480 | 6 | <0.35 | 0.05 | 76 | >480 | 6 |
| Epoxy propane, 1,2- | Liquid | 75-56-9 | 41 | 43 | 51 | 2 | <5 | 0.03 | 1860 | 114 | 3 |
| Ethane 1,2-diol | Liquid | 107-21-1 | >480 | >480 | >480 | 6 | <0.001 | 0.001 | <0.48 | >480 | 6 |
| Ethane dioic acid (sat) | Liquid | 144-62-7 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Ethane diol dipropanoate, 1,2- | Liquid | 123-73-9 | 121 | 147 | >480 | 6 | <1 | 0.02 | 210 | 405 | 5 |
| Ethane nitrile | Liquid | 75-05-8 | 65*/83 | 131 | >480 | 6 | <0.4 | 0.03 | <82 | >480 | 6 |
| Ethane thiol | Liquid | 75-08-1 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Ethane trichloride | Liquid | 79-00-5 | 120*/173 | 164*/232 | 202*/302 | 4 | 9.1 | 0.01 | | | |
| Ethanol | Liquid | 64-17-5 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Ethanol amine | Liquid | 141-43-5 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Ethanoyl chloride | Liquid | 75-36-5 | 155 | >480 | >480 | 6 | 0.0014 | 0.0001 | | | |
| Ethansulphonic acid (70%) | Liquid | 594-45-6 | >480 | >480 | >480 | 6 | <0.08 | 0.08 | <38.4 | >480 | 6 |
| Ethoxy ethanol, 2- | Liquid | 110-80-5 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Ethoxy ethylacetat | Liquid | 111-15-9 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Ethyl Cellosolve® | Liquid | 110-80-5 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Ethyl acetate | Liquid | 141-78-6 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Ethyl acrylate | Liquid | 140-88-5 | imm* /161 | imm* /162 | imm* /163 | | <5 | 0.04 | | | |
| Ethyl alcohol | Liquid | 64-17-5 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Ethyl benzene | Liquid | 100-41-4 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Ethyl ethanamine, N- | Liquid | 109-89-7 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Ethyl ether | Liquid | 60-29-7 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Ethyl glycol acetate | Liquid | 111-15-9 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Ethyl hexanoic acid | Liquid | 149-57-5 | >480 | >480 | >480 | 6 | <0.04 | 0.04 | <19.2 | >480 | 6 |
| Ethyl mercaptan | Liquid | 75-08-1 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Ethyl methyl carbonate (EMC) | Liquid | 623-53-0 | >480 | >480 | >480 | 6 | <0.019 | 0.019 | 0 | >480 | 6 |
| Ethyl nitrile | Liquid | 75-05-8 | 65*/83 | 131 | >480 | 6 | <0.4 | 0.03 | <82 | >480 | 6 |
| Ethylchloroformate | Liquid | 541-41-3 | >480 | >480 | >480 | 6 | <0.04 | 0.04 | <19.2 | >480 | 6 |
| Ethylene Carbonate solution (60%) | Liquid | 96-49-1 | >480 | >480 | >480 | 6 | <0.044 | 0.044 | 0 | >480 | 6 |
| Ethylene carboxylic acid | Liquid | 79-10-7 | >480 | >480 | >480 | 6 | <0.06 | 0.06 | <28.8 | >480 | 6 |
| Ethylene chlorohydrin | Liquid | 107-07-3 | >480 | >480 | >480 | 6 | <0.06 | 0.06 | <28.8 | >480 | 6 |
| Ethylene diamine | Liquid | 107-15-3 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Ethylene dibromide | Liquid | 106-93-4 | 84*/153 | 144*/288 | >480 | 6 | 0.52 | 0.001 | | | |
| Ethylene dichloride | Liquid | 107-06-2 | 65*/83 | 93 | 109 | 3 | <3 | 0.04 | 898 | 182 | 4 |
| Ethylene glycol | Liquid | 107-21-1 | >480 | >480 | >480 | 6 | <0.001 | 0.001 | <0.48 | >480 | 6 |
| Ethylene glycol mono ethyl ether acetate | Liquid | 111-15-9 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Ethylene glycol monobutyl ether | Liquid | 111-76-2 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Ethylene glycol monoethyl ether | Liquid | 110-80-5 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Ethylene glycol monomethyl ether | Liquid | 109-86-4 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |

| HAZARD / CHEMICAL NAME | PHYSICAL STATE | CAS | BT ACT | BT 0.1 | BT 1.0 | EN | SSPR | MDPR | CUM 480 | TIME 150 | ISO |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Ethylene glycol monomethyl ether acetate | Liquid | 110-49-6 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Ethylene oxide (gaseous) | Vapor | 75-21-8 | 106 | 126 | >480 | 6 | <0.35 | 0.05 | 76 | >480 | 6 |
| Ethylene tetrachloride | Liquid | 127-18-4 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Ethylene trichloride | Liquid | 79-01-6 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Ferric (II) chloride (sat) | Liquid | 7758-94-3 | >480 | >480 | >480 | 6 | <0.07 | 0.07 | <33.6 | >480 | 6 |
| Ferric (III) chloride (40%) | Liquid | 7705-08-0 | >480 | >480 | >480 | 6 | <0.03 | 0.03 | <14.4 | >480 | 6 |
| Fluorobenzene | Liquid | 462-06-6 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Fluorosilicic acid (33-35%) | Liquid | 16961-83-4 | >480 | >480 | >480 | 6 | <0.04 | 0.04 | <19.2 | >480 | 6 |
| Fluorosulfonic acid | Liquid | 7789-21-1 | 87 | 194 | >480 | 6 | na | 0.02 | 29 | >480 | 6 |
| Formaldehyde (37%) | Liquid | 50-00-0 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Formalin (37% (10-15% Methanol)) | Liquid | 50-00-0 | >480 | >480 | >480 | 6 | <0. 0048 | 0.0048 | <2.3 | >480 | 6 |
| Formalin (37%) | Liquid | 50-00-0 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Formic acid (50%) | Liquid | 64-18-6 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Formic acid (>95%) | Liquid | 64-18-6 | 172 | 260 | >480 | 6 | 0.24 | 0.001 | | | |
| Furaldehyde, 2- | Liquid | 98-01-1 | 459 | >480 | >480 | 6 | na | 0.03 | <14.4 | >480 | 6 |
| Furan | Liquid | 110-00-9 | 75 | 97 | >480 | 6 | <1 | 0.02 | 206 | 411 | 5 |
| Furfural | Liquid | 98-01-1 | 459 | >480 | >480 | 6 | na | 0.03 | <14.4 | >480 | 6 |
| Gasoline, leaded | Liquid | mix | imm | imm*/21 | | | 0.32 | 0.001 | | | |
| Gasoline, unleaded | Liquid | 86290-81-5 | >480 | >480 | >480 | 6 | <0.001 | 0.001 | <0.48 | >480 | 6 |
| Glutaral (50%) | Liquid | 111-30-8 | 150 | 170 | 200 | 4 | 1.861 | 0.01 | | | |
| Glutaraldehyde (50%) | Liquid | 111-30-8 | 150 | 170 | 200 | 4 | 1.861 | 0.01 | | | |
| Glycol alcohol | Liquid | 107-21-1 | >480 | >480 | >480 | 6 | <0.001 | 0.001 | <0.48 | >480 | 6 |
| Glycol chlorohydrin | Liquid | 107-07-3 | >480 | >480 | >480 | 6 | <0.06 | 0.06 | <28.8 | >480 | 6 |
| Green Liquor (mix) | Liquid | mix | | >480 | | | | | | | |
| Heptane | Liquid | 142-82-5 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Hexamethylene diamine (45 °C, molten) | Liquid | 124-09-4 | 423 | >480 | >480 | 6 | 0.003 | 0.0001 | <1.4 | >480 | 6 |
| Hexamethylene diisocyanate | Liquid | 822-06-0 | >480 | >480 | >480 | 6 | <0.0271 | 0.0271 | <13 | >480 | 6 |
| Hexane, n- | Liquid | 110-54-3 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Hexanone | Liquid | 108-94-1 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Hexone | Liquid | 108-10-1 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Hexyl chloro formate, 2- | Liquid | 6092-54-2 | >480 | >480 | >480 | 6 | <0.08 | 0.08 | <38.4 | >480 | 6 |
| Hydrazine | Liquid | 302-01-2 | 269 | 283 | 352 | 5 | 2.3 | 0.001 | | | |
| Hydriodic acid (55-57%) | Liquid | 10034-85-2 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Hydrobromic acid (48%) | Liquid | 10035-10-6 | >480 | >480 | >480 | 6 | <0.04 | 0.04 | <19.2 | >480 | 6 |
| Hydrochloric acid (37%) | Liquid | 7647-01-0 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Hydrofluoric acid (48-51%) | Liquid | 7664-39-3 | >480 | >480 | >480 | 6 | <0.025 | 0.025 | <12 | >480 | 6 |
| Hydrofluoric acid (60%) | Liquid | 7664-39-3 | 18 | 52 | 373 | 5 | na | 0.005 | | | |
| Hydrofluoric acid (70%) | Liquid | 7664-39-3 | 22 | 35 | 293 | 5 | na | 0.005 | 414 | 227 | 4 |
| Hydrogen bromide (gaseous) | Vapor | 10035-10-6 | >480 | >480 | >480 | 6 | <0.0001 | 0.0001 | <0.04 | >480 | 6 |
| Hydrogen chloride (gaseous) | Vapor | 7647-01-0 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Hydrogen fluoride (20-27 ° C, gaseous) | Vapor | 7664-39-3 | imm | imm | 23 | 1 | na | 0.05 | | | |
| Hydrogen peroxide (50%) | Liquid | 7722-84-1 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Hydrogen peroxide (70%) | Liquid | 7722-84-1 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |

| HAZARD / CHEMICAL NAME | PHYSICAL STATE | CAS | BT ACT | BT 0.1 | BT 1.0 | EN | SSPR | MDPR | CUM 480 | TIME 150 | ISO |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Hydroxy 1,2,3-propanetricarboxylic acid, 2- (sat) | Liquid | 77-92-9 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Hydroxy 1-ethanethiol, 2- | Liquid | 60-24-2 | >480 | >480 | >480 | 6 | <0.08 | 0.08 | <38.4 | >480 | 6 |
| Hydroxy 2-methylpropionitrile, 2- | Liquid | 75-86-5 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Hydroxy isobutyronitrile | Liquid | 75-86-5 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Hydroxy toluene | Liquid | 100-51-6 | >480 | >480 | >480 | 6 | <0.1 | 0.1 | <48 | >480 | 6 |
| Hydroxy toluene, o- | Liquid | 95-48-7 | 173 | 179 | 211 | 4 | <4 | 0.02 | 674 | 295 | 5 |
| Hypophosphorus acid (50%) | Liquid | 6303-21-5 | >480 | >480 | >480 | 6 | <0.09 | 0.09 | <43.2 | >480 | 6 |
| Iodomethane | Liquid | 74-88-4 | 254 | 296 | >480 | 6 | na | 0.07 | 53.6 | >480 | 6 |
| Isobutyl methyl ketone | Liquid | 108-10-1 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Isophthaloyldichloride (45 °C, molten) | Liquid | 99-63-8 | >480 | >480 | >480 | 6 | <0.0001 | 0.0001 | <0.04 | >480 | 6 |
| Isopropanol | Liquid | 67-63-0 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Isopropyl Acetate | Liquid | 108-21-4 | >480 | >480 | >480 | 6 | <0.1 | 0.033 | 0 | >480 | 6 |
| Isopropyl alcohol | Liquid | 67-63-0 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Isopropyl amine | Liquid | 75-31-0 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Isopropyl benzene | Liquid | 98-82-8 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Isopropyl bromoacetate (>95%) | Liquid | 29921-57-1 | >480 | >480 | >480 | 6 | <0.04 | 0.04 | <19.2 | >480 | 6 |
| Isopropylidenediphenol diglycidyl ether, 4,4'- | Liquid | 1675-54-3 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Kerosene | Liquid | 8008-20-6 | >480 | >480 | >480 | 6 | <0.001 | 0.001 | <0.48 | >480 | 6 |
| Ketone propane | Liquid | 67-64-1 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Lewisite (L), FINABEL 0.7.C | Liquid | 541-25-3 | >155[8] | >155[8] | | | | | | | |
| Lewisite (L), MIL-STD-282 (100 g/m$^2$) | Liquid | 541-25-3 | | 360[8] | | | | | | | |
| Limonene d- | Liquid | 5989-27-5 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Lithium Hexafluorophosphate (sat.) | Liquid | 21324-40-3 | >480 | >480 | >480 | 6 | <0.07 | 0.07 | <33.6 | >480 | 6 |
| MEK | Liquid | 78-93-3 | imm | 40*/64 | >480 | 6 | 0.36 | 0.001 | | | |
| Maleic anhydride (66 °C, molten) | Liquid | 108-31-6 | 21 | 22 | 24 | 1 | 24.6 | 0.016 | | | |
| Mercapto acetic acid | Liquid | 68-11-1 | >480 | >480 | >480 | 6 | <0.0001 | 0.0001 | <0.04 | >480 | 6 |
| Mercapto ethanol | Liquid | 60-24-2 | >480 | >480 | >480 | 6 | <0.08 | 0.08 | <38.4 | >480 | 6 |
| Mercuric I chloride (sat) | Liquid | 10112-91-1 | >480 | >480 | >480 | 6 | <0.1 | 0.1 | <48 | >480 | 6 |
| Mercury | Liquid | 7439-97-6 | >480 | >480 | >480 | 6 | <0.09 | 0.09 | <43.2 | >480 | 6 |
| Methacrylic acid | Liquid | 79-41-4 | >480 | >480 | >480 | 6 | <0.0001 | 0.0001 | <0.04 | >480 | 6 |
| Methallyl Alcohol | Liquid | 513-42-8 | >480 | >480 | >480 | 6 | <0.01 | 0.0116 | 0 | >480 | 6 |
| Methanesulfonyl chloride | Liquid | 124-63-0 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Methanesulphonic acid | Liquid | 75-75-2 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Methanethiol | Vapor | 74-93-1 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Methanol | Liquid | 67-56-1 | 56 | 117 | >480 | 6 | 0.14 | 0.02 | | | |
| Methoxy 2-methylpropane, 2- | Liquid | 1634-04-4 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Methoxy chloromethane | Liquid | 107-30-2 | imm*/11 | imm*/37 | >480 | 6 | 0.75 | 0.001 | | | |
| Methoxy ethanol, 2 | Liquid | 109-86-4 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Methoxy ethylacetate, 2- | Liquid | 110-49-6 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Methyl -2-pyridyl acetate | Liquid | 1658-42-0 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |

| HAZARD / CHEMICAL NAME | PHYSICAL STATE | CAS | BT ACT | BT 0.1 | BT 1.0 | EN | SSPR | MDPR | CUM 480 | TIME 150 | ISO |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Methyl 1,5-pentantedinitrile, 2- | Liquid | 4553-62-2 | >480 | >480 | >480 | 6 | <0.1 | 0.1 | <48 | >480 | 6 |
| Methyl 2-methyl-2-propenoate | Liquid | 80-62-6 | imm*/26 | imm*/53 | | | 1.4 | 0.001 | | | |
| Methyl 2-pyrrolidone, N- | Liquid | 872-50-4 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Methyl 4-isopropenyl-1-cyclohexene, 1- | Liquid | 5989-27-5 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Methyl Ethyl Ketone Peroxide (35%) | Liquid | 1338-23-4 | >480 | >480 | >480 | 6 | <0.018 | 0.018 | <10 | >480 | 6 |
| Methyl N-nitrosomethanamine, N- | Liquid | 62-75-9 | >480 | >480 | >480 | 6 | <0.001 | 0.001 | <0.48 | >480 | 6 |
| Methyl acetyl | Liquid | 67-64-1 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Methyl acrolein | Liquid | 123-73-9 | 121 | 147 | >480 | 6 | <1 | 0.02 | 210 | 405 | 5 |
| Methyl acrylate | Liquid | 96-33-3 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Methyl amine (gaseous) | Vapor | 74-89-5 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Methyl aniline, o- | Liquid | 95-53-4 | >480 | >480 | >480 | 6 | <0.03 | 0.03 | <14.4 | >480 | 6 |
| Methyl benzol | Liquid | 108-88-3 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Methyl benzylamine, N- | Liquid | 103-67-3 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Methyl chloride (gaseous) | Vapor | 74-87-3 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Methyl chloro formate | Liquid | 79-22-1 | 99*/175 | 204*/308 | >480 | 6 | 0.17 | 0.05 | <24 | >480 | 6 |
| Methyl cyanide | Liquid | 75-05-8 | 65*/83 | 131 | >480 | 6 | <0.4 | 0.03 | <82 | >480 | 6 |
| Methyl ethyl ketone | Liquid | 78-93-3 | imm | 40*/64 | >480 | 6 | 0.36 | 0.001 | | | |
| Methyl ethyl ketoxime | Liquid | 96-29-7 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Methyl formamide, N- | Liquid | 123-39-7 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Methyl hydrazine | Liquid | 60-34-4 | 83*/206 | 183*/283 | 280*/413 | 5 | 0.98 | 0.01 | | | |
| Methyl imidazole, 1- | Liquid | 616-47-7 | >480 | >480 | >480 | 6 | <0.06 | 0.06 | <28.8 | >480 | 6 |
| Methyl iodide | Liquid | 74-88-4 | 254 | 296 | >480 | 6 | na | 0.07 | 53.6 | >480 | 6 |
| Methyl isocyanate | Liquid | 624-83-9 | imm | imm | | | 0.42 | 0.001 | | | |
| Methyl ketone | Liquid | 67-64-1 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Methyl mercaptan | Vapor | 74-93-1 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Methyl methacrylate | Liquid | 80-62-6 | imm*/26 | imm*/53 | | | 1.4 | 0.001 | | | |
| Methyl pentan-2-one, 4- | Liquid | 108-10-1 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Methyl phenols | Liquid | 1319-77-3 | >480 | >480 | >480 | 6 | <0.03 | 0.03 | <14.4 | >480 | 6 |
| Methyl propan-2-ol, 2- | Liquid | 75-65-0 | 10*/147 | 37*/205 | >480 | 6 | 0.26 | 0.02 | | | |
| Methyl propenoic acid, 2- | Liquid | 79-41-4 | >480 | >480 | >480 | 6 | <0.0001 | 0.0001 | <0.04 | >480 | 6 |
| Methyl pyridine, 2- | Liquid | 109-06-8 | >480 | >480 | >480 | 6 | <0.024 | 0.024 | <11.5 | >480 | 6 |
| Methyl pyridine, 3- | Liquid | 108-99-6 | >480 | >480 | >480 | 6 | <0.024 | 0.024 | <11.5 | >480 | 6 |
| Methyl tert-butyl ether | Liquid | 1634-04-4 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Methyl trichlorosilane | Liquid | 75-79-6 | >480 | >480 | >480 | 6 | <0.0001 | 0.0001 | <0.04 | >480 | 6 |
| Methyl vinyl ketone | Liquid | 78-94-4 | 287*/379 | >480 | >480 | 6 | <0.1 | 0.02 | <9.6 | >480 | 6 |
| Methylcyclohexane | Liquid | 108-87-2 | >480 | >480 | >480 | 6 | <0.04 | 0.04 | <20 | >480 | 6 |
| Methylen Isocyclohexylamine, 4,4- (40 °C) | Liquid | 1761-71-3 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Methylene bromide | Liquid | 74-95-3 | imm | imm | 20 | 1 | 111 | 0.05 | | | |
| Methylene chloride | Liquid | 75-09-2 | imm | imm | imm | | 23.7 | 0.03 | | | |
| Methylene chloride (10.000 ppm) | Vapor | 75-09-2 | imm | 52 | >480 | 6 | <0.21 | 0.05 | 100 | >480 | 6 |
| Methylene chloride (1000 ppm) | Vapor | 75-09-2 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |

| HAZARD / CHEMICAL NAME | PHYSICAL STATE | CAS | BT ACT | BT 0.1 | BT 1.0 | EN | SSPR | MDPR | CUM 480 | TIME 150 | ISO |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Methylene diphenyl diisocyanate, 4,4'- (50 °C, molten) | Liquid | 101-68-8 | >480 | >480 | >480 | 6 | <0.0403 | 0.0403 | <19.3 | >480 | 6 |
| Naphthalene | Solid | 91-20-3 | >480 | >480 | >480 | 6 | <0.001 | 0.001 | <0.48 | >480 | 6 |
| Naphthalene (25% in Diethylene glycol dimethylether) | Liquid | 91-20-3 | >480 | >480 | >480 | 6 | <0.007 | 0.007 | <3.4 | >480 | 6 |
| Neoprene (50% in Butanol) | Liquid | 126-99-8 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Nicotine | Liquid | 54-11-5 | >480 | >480 | >480 | 6 | <0.1 | 0.1 | <48 | >480 | 6 |
| Nitric acid (70%) | Liquid | 7697-37-2 | >480 | >480 | >480 | 6 | <0.04 | 0.04 | <19.2 | >480 | 6 |
| Nitric acid (>95%) | Liquid | 7697-37-2 | 14*/19 | 46 | 65*/82 | 3 | <8 | <0.03 | 34/90 min | 134 | 4 |
| Nitric acid, red fuming (90%) | Liquid | 52583-42-3 | imm | imm*/10 | 32 | 2 | na | 0.08 | 342/80 min | 59 | 2 |
| Nitro benzene | Liquid | 98-95-3 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Nitro chlormethan | Liquid | 76-06-2 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Nitro methane | Liquid | 75-52-5 | 157 | 233 | | | 0.97 | 0.001 | | | |
| Nitro propane, 2- | Liquid | 79-46-9 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Nitro toluene, 2- | Liquid | 88-72-2 | >480 | >480 | >480 | 6 | <0.03 | 0.03 | <14.4 | >480 | 6 |
| Nitrogen dioxide | Vapor | 10102-44-0 | <15 | <15 | | | >0.2 | 0.01 | | | |
| Norflurane | Vapor | 811-97-2 | >480 | >480 | >480 | 6 | <0.04 | 0.04 | <19.2 | >480 | 6 |
| Octyl chlor formiate | Liquid | 7452-59-7 | >480 | >480 | >480 | 6 | <0.06 | 0.06 | <28.8 | >480 | 6 |
| Oleum (20% free SO3) | Liquid | 8014-95-7 | >480 | >480 | >480 | 6 | <0.06 | 0.06 | <28.8 | >480 | 6 |
| Oleum (40% free SO3) | Liquid | 8014-95-7 | 130*/220 | 455*/468 | >480 | 6 | 0.32 | 0.0001 | | | |
| Oleum (65% free SO3) | Liquid | 8014-95-7 | 180 | 248 | 370 | 5 | na | 0.04 | 398 | 428 | 5 |
| Oxalic acid (sat) | Liquid | 144-62-7 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| PCB in transformer oil (mix) | Liquid | mix | 324*/428 | >480 | >480 | 6 | 0.032 | 0.01 | | | |
| Pentachloroantimony | Liquid | 7647-18-9 | <15 | <15 | <15 | 1 | >10 | 0.1 | | | |
| Pentanedial, 1,5- (50%) | Liquid | 111-30-8 | 150 | 170 | 200 | 4 | 1.861 | 0.01 | | | |
| Pentanoic acid | Liquid | 109-52-4 | >480 | >480 | >480 | 6 | <0.03 | 0.03 | <14.4 | >480 | 6 |
| Pentanol, 1- | Liquid | 71-41-0 | >480 | >480 | >480 | 6 | <0.1 | 0.1 | <48 | >480 | 6 |
| Pentanol, tert- | Liquid | 75-85-4 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Pentene nitrile, 2- | Liquid | 13284-42-9 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Pentyl acetate | Liquid | 628-63-7 | >480 | >480 | >480 | 6 | 0.007 | 0.001 | <10.2 | >480 | 6 |
| Peracetic Acid (32%) | Liquid | 79-21-0 | >480 | >480 | >480 | 6 | <0.0123 | 0.0123 | <6 | >480 | 6 |
| Perchloric acid (70%) | Liquid | 7601-90-3 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Phenethylene | Liquid | 100-42-5 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Phenol (45 °C, molten) | Liquid | 108-95-2 | 22 | 25 | 29 | 1 | na | 0.05 | >355, 120 min | 56 | 2 |
| Phenol (60 °C, molten) | Liquid | 108-95-2 | imm | imm | imm | | na | 0.01 | 426/24 min | 14 | 1 |
| Phenol (85%) | Liquid | 108-95-2 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Phenyl acetonitrile | Liquid | 140-29-4 | >390 | >390 | >390 | 5 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Phenyl amine | Liquid | 62-53-3 | >480 | >480 | >480 | 6 | <0.03 | 0.03 | <14.4 | >480 | 6 |
| Phenyl chlor formiate | Liquid | 1885-14-9 | >480 | >480 | >480 | 6 | <0.06 | 0.06 | <28.8 | >480 | 6 |
| Phenyl chloride | Liquid | 108-90-7 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Phenyl cyanide | Liquid | 100-47-0 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Phenyl ethane | Liquid | 100-41-4 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Phenyl ethanol, 1- | Liquid | 98-85-1 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Phenyl propane, 2- | Liquid | 98-82-8 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Phenyl trichlorosilane | Liquid | 98-13-5 | >480 | >480 | >480 | 6 | <0.0001 | 0.0001 | <0.04 | >480 | 6 |

| HAZARD / CHEMICAL NAME | PHYSICAL STATE | CAS | BT ACT | BT 0.1 | BT 1.0 | EN | SSPR | MDPR | CUM 480 | TIME 150 | ISO |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Phosgene | Vapor | 75-44-5 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Phosphine | Vapor | 7803-51-2 | imm | imm | | | >0.11 | 0.003 | | | |
| Phosphinic acid (50%) | Liquid | 6303-21-5 | >480 | >480 | >480 | 6 | <0.09 | 0.09 | <43.2 | >480 | 6 |
| Phosphoric acid (85%) | Liquid | 7664-38-2 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Phosphorus oxychloride | Liquid | 10025-87-3 | | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Phosphorus trichloride | Liquid | 7719-12-2 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Picoline, 2- | Liquid | 109-06-8 | >480 | >480 | >480 | 6 | <0.024 | 0.024 | <11.5 | >480 | 6 |
| Picoline, 3- | Liquid | 108-99-6 | >480 | >480 | >480 | 6 | <0.024 | 0.024 | <11.5 | >480 | 6 |
| Pimelic ketone | Liquid | 108-94-1 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Polymethylene polyphenyle isocyanate (p-MDI) | Liquid | 9016-87-9 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Potassium acetate (sat) | Liquid | 127-08-2 | >480 | >480 | >480 | 6 | <0.07 | 0.07 | <33.6 | >480 | 6 |
| Potassium chromate (sat) | Liquid | 7789-00-6 | >480 | >480 | >480 | 6 | <0.08 | 0.08 | <38.4 | >480 | 6 |
| Potassium hydroxide (45%) | Liquid | 1310-58-3 | >480 | >480 | >480 | 6 | <0.023 | 0.023 | <11 | >480 | 0 |
| Potassium hydroxide (50%) | Liquid | 1310-58-3 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Prop-2-en-1-al | Liquid | 107-02-8 | 51*/65 | 75*/101 | >480 | 6 | <0.5 | 0.02 | 105 | >480 | 6 |
| Prop-2-en-1-al (10 g/m$^2$) | Liquid | 107-02-8 | >480 | >480 | >480 | 6 | <0.04 | 0.04 | <19.2 | >480 | 6 |
| Prop-2-yn-1-ol | Liquid | 107-19-7 | 123 | 123 | 127 | 4 | 37.9 | 0.07 | | | |
| Propan -1-ol | Liquid | 71-23-8 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Propan -2-ol | Liquid | 67-63-0 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Propan -2-one | Liquid | 67-64-1 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Propanoic acid | Liquid | 79-09-4 | >480 | >480 | >480 | 6 | <0.03 | 0.03 | <14.4 | >480 | 6 |
| Propanol, 1- | Liquid | 71-23-8 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Propanol, n- | Liquid | 71-23-8 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Propargyl alcohol | Liquid | 107-19-7 | 123 | 123 | 127 | 4 | 37.9 | 0.07 | | | |
| Propen 1-ol, 2- | Liquid | 107-18-6 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Propenamide (50%) | Liquid | 79-06-1 | >480 | >480 | >480 | 6 | <0.1 | 0.1 | <48 | >480 | 6 |
| Propene acid | Liquid | 79-10-7 | >480 | >480 | >480 | 6 | <0.06 | 0.06 | <28.8 | >480 | 6 |
| Propenenitrile, 2- | Liquid | 107-13-1 | 72*/91 | 73*/92 | 103 | 3 | 8.9 | 0.0085 | | | |
| Propenoic acid butyl ester, 2- | Liquid | 141-32-2 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | >480 | >480 | 6 |
| Propenoic acid nitrile | Liquid | 107-13-1 | 72*/91 | 73*/92 | 103 | 3 | 8.9 | 0.0085 | | | |
| Propychloroformate | Liquid | 109-61-5 | >480 | >480 | >480 | 6 | <0.03 | 0.03 | <14.4 | >480 | 6 |
| Propyl alcohol | Liquid | 71-23-8 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Propyl amine, n- | Liquid | 107-10-8 | imm | 16*/21 | >480 | 6 | 0.52 | 0.05 | | | |
| Propyl bromide, n- | Liquid | 106-94-5 | >480 | >480 | >480 | 6 | <0.03 | 0.03 | <14.4 | >480 | 6 |
| Propylene aldehyde | Liquid | 123-73-9 | 121 | 147 | >480 | 6 | <1 | 0.02 | 210 | 405 | 5 |
| Propylene oxide, 1,2- | Liquid | 75-56-9 | 41 | 43 | 51 | 2 | <5 | 0.03 | 1860 | 114 | 3 |
| Pyridene, 2-fluoro-6-(trifluoromethyl) | Liquid | 94239-04-0 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Pyridine | Liquid | 110-86-1 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Pyroacetic ether | Liquid | 67-64-1 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Pyrrolidine | Liquid | 123-75-1 | 40*/80 | 45*/100 | 145*/185 | 4 | 4.7 | 0.05 | | | |
| Sarin (GB), FINABEL 0.7.C | Liquid | 107-44-8 | | >1400[8] | | | | | | | |
| Sarin (GB), MIL-STD-282 (100 g/m$^2$) | Liquid | 107-44-8 | | >480[8] | | | | | | | |
| Silane | Vapor | 7803-62-5 | >480 | >480 | >480 | 6 | <0.1 | 0.1 | <48 | >480 | 6 |

| HAZARD / CHEMICAL NAME | PHYSICAL STATE | CAS | BT ACT | BT 0.1 | BT 1.0 | EN | SSPR | MDPR | CUM 480 | TIME 150 | ISO |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Silicon tetrachloride | Liquid | 10026-04-7 | >480 | >480 | >480 | 6 | <0.0001 | 0.0001 | <0.04 | >480 | 6 |
| Sodium bisulphite (38-40%) | Liquid | 7631-90-5 | >480 | >480 | >480 | 6 | <0.07 | 0.07 | <33.6 | >480 | 6 |
| Sodium cyanide (45%) | Liquid | 143-33-9 | >480 | >480 | >480 | 6 | <0.1 | 0.1 | <48 | >480 | 6 |
| Sodium cyanide (sat) | Liquid | 143-33-9 | >480 | >480 | >480 | 6 | <0.07 | 0.07 | <33.6 | >480 | 6 |
| Sodium hydroxide (50% at 50 °C) | Liquid | 1310-73-2 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Sodium hydroxide (50%) | Liquid | 1310-73-2 | >480 | >480 | >480 | 6 | <0.025 | 0.025 | <12 | >480 | 6 |
| Sodium hypochlorite (15%) | Liquid | 7681-52-9 | >480 | >480 | >480 | 6 | <0.03 | 0.03 | <14.4 | >480 | 6 |
| Soman (GD), FINABEL 0.7.C | Liquid | 96-64-0 | | >1400[8] | | | | | | | |
| Soman (GD), MIL-STD-282 (100 g/m$^2$) | Liquid | 96-64-0 | | >480[8] | | | | | | | |
| Spiritus | Liquid | 64-17-5 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Styrene | Liquid | 100-42-5 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Sulfamic acid (15%) | Liquid | 5329-14-6 | >480 | >480 | >480 | 6 | <0.04 | 0.04 | <19.2 | >480 | 6 |
| Sulfamidic acid (15%) | Liquid | 5329-14-6 | >480 | >480 | >480 | 6 | <0.04 | 0.04 | <19.2 | >480 | 6 |
| Sulfur Mustard (HD), FINABEL 0.7.C | Liquid | 505-60-2 | | >1400[8] | | | | | | | |
| Sulfur Mustard (HD), MIL-STD-282 (100 g/m$^2$) | Liquid | 505-60-2 | | >480[8] | | | | | | | |
| Sulfur dioxide | Vapor | 7446-09-5 | 28*/46 | 28*/46 | >480 | 6 | <0.5 | 0.1 | <94 | >480 | 6 |
| Sulfuric acid (98% at 50 ° C) | Liquid | 7664-93-9 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Sulfuric acid (>95%) | Liquid | 7664-93-9 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Sulfuric acid diethyl ester | Liquid | 64-67-5 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Sulfuric acid dimethyl ester | Liquid | 77-78-1 | >480 | >480 | >480 | 6 | <0.09 | 0.09 | <43.2 | >480 | 6 |
| Sulfuric acid fuming (20% free SO3) | Liquid | 8014-95-7 | >480 | >480 | >480 | 6 | <0.06 | 0.06 | <28.8 | >480 | 6 |
| Sulfuric acid fuming (40% free SO3) | Liquid | 8014-95-7 | 130*/220 | 455*/468 | >480 | 6 | 0.32 | 0.0001 | | | |
| Sulfuric acid fuming (65% free SO3) | Liquid | 8014-95-7 | 180 | 248 | 370 | 5 | na | 0.04 | 398 | 428 | 5 |
| Sulfuryl chloride | Liquid | 7791-25-5 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Tabun (GA), FINABEL 0.7.C | Liquid | 77-81-6 | | >1400[8] | | | | | | | |
| Tabun (GA), MIL-STD-282 (100 g/m$^2$) | Liquid | 77-81-6 | | >480[8] | | | | | | | |
| Tetrachloro bisphenol-A, 2,2',6,6'- | Solid | 79-95-8 | >480 | >480 | >480 | 6 | <0.1 | 0.1 | <48 | >480 | 6 |
| Tetrachloro ethane, 1,1,2,2,- | Liquid | 79-34-5 | >480 | >480 | >480 | 6 | <0.008 | 0.008 | <3.8 | >480 | 6 |
| Tetrachloro ethylene, 1,1,2,2- | Liquid | 127-18-4 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Tetrachloro methane | Liquid | 56-23-5 | imm | imm*/11 | >480 | 6 | 0.57 | 0.001 | | | |
| Tetrachloro methane (1000 ppm) | Vapor | 56-23-5 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Tetraethylene pentamine | Liquid | 112-57-2 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Tetrafluoroethane, 1,1,1,2- | Vapor | 811-97-2 | >480 | >480 | >480 | 6 | <0.04 | 0.04 | <19.2 | >480 | 6 |
| Tetrahydrofuran | Liquid | 109-99-9 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Tetramethyl ammonium hydroxide (25%) | Liquid | 75-59-2 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Thiazol, 1,3- | Liquid | 288-47-1 | >480 | >480 | >480 | 6 | <0.04 | 0.04 | <19.2 | >480 | 6 |
| Thioalkohol | Liquid | 75-08-1 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Thioglycolic acid | Liquid | 68-11-1 | >480 | >480 | >480 | 6 | <0.0001 | 0.0001 | <0.04 | >480 | 6 |

| HAZARD / CHEMICAL NAME | PHYSICAL STATE | CAS | BT ACT | BT 0.1 | BT 1.0 | EN | SSPR | MDPR | CUM 480 | TIME 150 | ISO |
|---|---|---|---|---|---|---|---|---|---|---|---|
| Thionyl chloride | Liquid | 7719-09-7 | 21 | 21 | 33 | 2 | nm | 0.1 | nm | 47 | 2 |
| Thiophene | Liquid | 110-02-1 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Tin chloride, mono-n-butyl | Liquid | 1118-46-3 | >480 | >480 | >480 | 6 | <0.0001 | 0.0001 | <0.04 | >480 | 6 |
| Tin chloride, tri-n-butyl | Liquid | 1461-22-9 | | nm | >480 | 6 | nm | 0.2 | | | |
| Titan(IV) chloride | Liquid | 7550-45-0 | >480 | >480 | >480 | 6 | <0.0001 | 0.0001 | <0.04 | >480 | 6 |
| Titanium (IV) isopropoxide | Liquid | 546-68-9 | >480 | >480 | >480 | 6 | <0.1 | 0.002 | 0 | >480 | 6 |
| Titanium tetrachloride | Liquid | 7550-45-0 | >480 | >480 | >480 | 6 | <0.0001 | 0.0001 | <0.04 | >480 | 6 |
| Toluene | Liquid | 108-88-3 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Toluene diisocyanate, 2,4- | Liquid | 584-84-9 | >480 | >480 | >480 | 6 | <0.0281 | 0.0281 | <13.5 | >480 | 6 |
| Toluene diisocyanate, 2,4- (80%) | Liquid | 584-84-9 | >480 | >480 | >480 | 6 | <0.0281 | 0.0281 | <13.5 | >480 | 6 |
| Toluidine, o- | Liquid | 95-53-4 | >480 | >480 | >480 | 6 | <0.03 | 0.03 | <14.4 | >480 | 6 |
| Tributyl amine (95%) | Liquid | 102-82-9 | >480 | >480 | >480 | 6 | <0.04 | 0.04 | <19.2 | >480 | 6 |
| Tributyl phosphate | Liquid | 126-73-8 | >480 | >480 | >480 | 6 | <0.1 | 0.037 | 0 | >480 | 6 |
| Trichloro acetic acid (sat) | Liquid | 76-03-9 | >480 | >480 | >480 | 6 | <0.03 | 0.03 | <14.4 | >480 | 6 |
| Trichloro acetone, 1,1,3- (87.7%) | Liquid | 921-03-9 | 431*/458 | 467*/476 | >480 | 6 | <0.2 | 0.05 | <24 | >480 | 6 |
| Trichloro benzene, 1,2,4- | Liquid | 120-82-1 | >480 | >480 | >480 | 6 | <0.001 | 0.001 | <0.48 | >480 | 6 |
| Trichloro ethane, 1,1,2- | Liquid | 79-00-5 | 120*/173 | 164*/232 | 202*/302 | 4 | 9.1 | 0.01 | | | |
| Trichloro ethanol, 2,2,2- | Liquid | 115-20-8 | >480 | >480 | >480 | 6 | <0.008 | 0.008 | <3.8 | >480 | 6 |
| Trichloro ethylene | Liquid | 79-01-6 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Trichloro methane | Liquid | 67-66-3 | imm | imm | imm | | 10.6 | 0.001 | | | |
| Trichloro methane (1000 ppm) | Vapor | 67-66-3 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Trichloro phenylsilane | Liquid | 98-13-5 | >480 | >480 | >480 | 6 | <0.0001 | 0.0001 | <0.04 | >480 | 6 |
| Triethyl amine | Liquid | 121-44-8 | >480 | >480 | >480 | 6 | 0.05 | 0.05 | <24 | >480 | 6 |
| Triethylentetramine (60%) | Liquid | 112-24-3 | >480 | >480 | >480 | 6 | <0.005 | 0.005 | <2.4 | >480 | 6 |
| Trifluoro acetic acid | Liquid | 76-05-1 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Trifluoro methansulfonic acid | Liquid | 1493-13-6 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Trimethyl chinon (30 °C, molten) | Liquid | 935-92-2 | | nm | >480 | 6 | nm | 0.05 | | | |
| VX Nerve Agent, FINABEL 0.7.C | Liquid | 50782-69-9 | | >1400[8] | | | | | | | |
| VX Nerve Agent, MIL-STD-282 (100 g/m$^2$) | Liquid | 50782-69-9 | | >480[8] | | | | | | | |
| Vinyl acetate | Liquid | 108-05-4 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Vinyl benzol | Liquid | 100-42-5 | >480 | >480 | >480 | 6 | <0.05 | 0.05 | <24 | >480 | 6 |
| Vinyl carbinol | Liquid | 107-18-6 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Vinyl chloride | Vapor | 75-01-4 | imm | >480 | >480 | 6 | 0.02 | 0.001 | <9.6 | >480 | 6 |
| Vinyl cyanide | Liquid | 107-13-1 | 72*/91 | 73*/92 | 103 | 3 | 8.9 | 0.0085 | | | |
| Vinyl ethylene (gaseous) | Vapor | 106-99-0 | >480 | >480 | >480 | 6 | <0.01 | 0.01 | <4.8 | >480 | 6 |
| Vinylidene chloride | Liquid | 75-35-4 | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| White Liquor | Liquid | mix | | >480 | | | | | | | |
| White spirit | Liquid | mix | >480 | >480 | >480 | 6 | <0.02 | 0.02 | <9.6 | >480 | 6 |
| Xylene, mixed isomers | Liquid | 1330-20-7 | >480 | >480 | >480 | 6 | <0.001 | 0.001 | <0.48 | >480 | 6 |
| Xylidine, 2,4- | Liquid | 95-68-1 | >480 | >480 | >480 | 6 | <0.0195 | 0.0195 | <9.4 | >480 | 6 |

BTAct (Actual) Breakthrough time at MDPR [mins] | BT0.1 Normalized breakthrough time at 0.1 µg/cm²/min [mins] |

BT1.0 Normalized breakthrough time at 1.0 µg/cm²/min [mins] | EN Classification according to EN 14325 | SSPR Steady state permeation rate [µg/cm²/min] |

MDPR Minimum detectable permeation rate [µg/cm²/min] | CUM480 Cumulative permeation mass after 480 mins [µg/cm²] |

Time150 Time to reach cumulative permeation mass of 150 µg/cm² [mins] | ISO Classification according to ISO 16602 |

CAS Chemical abstracts service registry number | min Minute | > Larger than | < Smaller than | imm Immediate (< 10 min) | nm Not tested |

sat Saturated solution | N/A Not Applicable | na Not attained | GPR grade General purpose reagent grade | * Based on lowest single value |

8 Actual breakthrough time; normalized breakthrough time is not available | DOT5 Degradation after 5 min | DOT30 Degradation after 30 min |

DOT60 Degradation after 60 min | DOT240 Degradation after 240 min | BT1383 Normalized breakthrough time at 0.1 µg/cm²/min [mins] acc. ASTM F1383 |

Important Note

Die veröffentlichten Permeationsdaten wurden von unabhängigen, akkreditierten Testlaboren entsprechend der zum betreffenden Zeitpunkt jeweils geltenden Testmethode (EN ISO 6529 (Methoden A und B), ASTM F739, ASTM F1383, ASTM D6978, EN369, EN 374-3) für DuPont generiert. Die Daten stellen in der Regel den Durchschnittswert von drei getesteten Materialproben dar. Alle Chemikalien wurden anhand einer Probe von mehr als 95 % (w/w) getestet, sofern nicht anders angegeben. Die Tests wurden zwischen 20 °C und 27 °C und unter Umgebungsdruck durchgeführt, sofern nicht anders angegeben. Eine hiervon abweichende Temperatur kann erheblichen Einfluss auf die Durchbruchszeit haben. Die Permeation nimmt in der Regel mit steigender Temperatur zu. Die kumulativen Permeationsdaten wurden gemessen oder auf Basis der niedrigsten nachweisbaren Permeationsrate berechnet. Die Tests auf Zytostatika wurden bei einer Testtemperatur von 27 °C nach ASTM D6978 oder ISO 6529 durchgeführt, mit der zusätzlichen Anforderung, eine normale Durchbruchszeit bei 0,01 µg /cm²/min aufzuzeichnen. Chemische Kampfstoffe (Lewisit, Sarin, Soman, Senfgas, Tabun und Nervengas VX) wurden nach MIL-STD-282 bei 22 °C oder nach FINABEL 0.7 bei 37 °C durchgeführt. Die Permeationsdaten für Tyvek® sind ausschließlich für weißes Tyvek® 500 und Tyvek® 600 gültig. Sie sind nicht für andere Tyvek®-Ausführungen oder -Farben gültig. Pemeationsdaten werden gewöhnlich für einzelne Chemikalien getestet. Die Permeationsmerkmale von Mischungen können sich häufig beträchtlich vom Verhalten der einzelnen Chemikalien unterscheiden. Die veröffentlichten Permeationsdaten für Handschuhe wurden nach ASTM F739 und ASTM F1383 generiert. Die veröffentlichten Degradationsdaten für Handschuhe wurden auf Grundlage einer gravimetrischen Methode generiert.

Bei dieser Art von Degradationstests wird eine Seite des Handschuhmaterials vier Stunden lang der Testchemikalie ausgesetzt. Der Prozentsatz der Gewichtsveränderung nach der Aussetzung wird in vier Zeitintervallen gemessen: 5, 30, 60 und 240 Minuten. Degradationseinstufungen:

- E: EXCELLENT (Ausgezeichnet, 0–10 % Gewichtsveränderung)
- G: GOOD (GUT, 11 – 20 % Gewichtsveränderung)
- F:FAIR (Ausreichend, 21 – 30 % Gewichtsveränderung)
- P: POOR (Gering, 31–50 % Gewichtsveränderung
- NR: NOT Recommended (Nicht Empfohlen, Mehr als 50 % Gewichtsveränderung)
- NT: NOT Tested (NICHT GETESTET)

Als Degradation wird die physische Veränderung eines Materials nach einer Aussetzung gegenüber Chemikalien bezeichnet. Zu den Effekten, die typischerweise beobachtet werden können, gehören Anschwellen, Faltenbildung, Verschlechterung (der Eigenschaften) oder Delaminierung. Es kann auch zu Verlusten der Reißfestigkeit kommen.

Bitte verwenden Sie die angegebenen Permeationsdaten im Rahmen der Risikobewertung, um die Auswahl eines für Ihre Anwendung geeigneten Schutzgewebes, Schutzkleidungsstücks, Handschuhs oder Zubehörs zu unterstützen. Die Durchbruchszeit ist nicht mit der Zeit identisch, während der ein Kleidungsstück sicher getragen werden kann. Durchbruchszeiten zeigen die Barrierewirkung an. Die Ergebnisse können jedoch je nach Testmethode und Testlabor unterschiedlich sein. Die Durchbruchszeit alleine ist nicht ausreichend, um zu ermitteln, wie lange ein Kleidungsstück nach einer Kontamination weiter getragen werden kann. Die Zeit, während der ein Benutzer das betreffende Kleidungsstück sicher tragen kann, kann kürzer oder länger sein, abhängig vom Permeationsverhalten und der Toxizität der Substanz, den Arbeitsbedingungen und den Aussetzungsbedingungen (z. B. Temperatur, Druck, Konzentration, physischer Zustand).

Letzte Aktualisierung der Permeationsdaten: 10/24/2022

Die hierin enthaltenen Informationen entsprechen unserem Kenntnisstand am Tag der Veröffentlichung. Wir behalten uns vor, die Informationen zu ändern, sofern neue Erkenntnisse und Erfahrungen erhältlich sind. Die hierin enthaltenen Daten entsprechen den üblichen Produkteigenschaften und beziehen sich ausschließlich auf das jeweilige Material; die Daten können unter Umständen nicht gelten, sofern die Materialien in Kombination mit anderen Materialien, Zusätzen oder in anderen Prozessen genutzt werden, sofern nicht ausdrücklich anderweitig angegeben. Die Daten sind nicht gedacht, Spezifikationsgrenzen festzulegen oder allein als Grundlage für ein Design; sie sind nicht dazu gedacht, Tests zu ersetzen, die von dem Anwender durchzuführen sind, um sich von der Eignung eines bestimmten Materials für einen speziellen Zweck zu überzeugen. Da DuPont nicht alle Variationen des endgültigen Gebrauches berücksichtigen kann, übernimmt DuPont keine Gewährleistung und keine Haftung im Zusammenhang mit der Nutzung der Informationen. Diese Publikation stellt keine Gewährung einer Lizenz oder eine Empfehlung zur Verletzung von Patentrechten dar.

WARNING

The garment does not protect against ionizing radiation.

This garment and/or fabric are not flame resistant and should not be used around heat, open flame, sparks or in potentially flammable environments.

The information provided herein corresponds to our knowledge on the subject at the date of its publication. This information may be subject to revision as new knowledge and experience becomes available. The data provided fall within the normal range of product properties and relate only to the specific material designated; these data may not be valid for such material used in combination with any other materials or additives or in any process, unless expressly indicated otherwise. The data provided should not be used to establish specification limits or used alone as the basis of design; they are not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of a specific material for your particular purposes. Since DuPont cannot anticipate all variations in actual end-use conditions DuPont makes no warranties and assumes no liability in connection with any use of this information. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent rights..

## DuPont™ SafeSPEC™ - We're here to help

Our powerful web-based tool can assist you with finding the appropriate DuPont garments for chemical and controlled environment hazards.

DuPont Personal Protection SafeSPEC™

DuPont Personal Protection

DuPont Personal Protection

**CREATED ON: JULY 16, 2026**

© 2024 DuPont. All rights reserved. DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™,℠ or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted.